Natural Gas Fuel for the 21st Century

Vaclav Smil



Ţ

Natural Gas

Natural Gas

Fuel for the 21st Century

Vaclav Smil



This edition first published 2015 © 2015 John Wiley & Sons, Ltd

Registered Office John Wiley & Sons, Ltd, The Atrium, Southern Gate, Chichester, West Sussex, PO19 8SQ, United Kingdom

For details of our global editorial offices, for customer services and for information about how to apply for permission to reuse the copyright material in this book please see our website at www.wiley.com.

The right of the author to be identified as the author of this work has been asserted in accordance with the Copyright, Designs and Patents Act 1988.

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording or otherwise, except as permitted by the UK Copyright, Designs and Patents Act 1988, without the prior permission of the publisher.

Wiley also publishes its books in a variety of electronic formats. Some content that appears in print may not be available in electronic books.

Designations used by companies to distinguish their products are often claimed as trademarks. All brand names and product names used in this book are trade names, service marks, trademarks or registered trademarks of their respective owners. The publisher is not associated with any product or vendor mentioned in this book.

Limit of Liability/Disclaimer of Warranty: While the publisher and author have used their best efforts in preparing this book, they make no representations or warranties with respect to the accuracy or completeness of the contents of this book and specifically disclaim any implied warranties of merchantability or fitness for a particular purpose. It is sold on the understanding that the publisher is not engaged in rendering professional services and neither the publisher nor the author shall be liable for damages arising herefrom. If professional advice or other expert assistance is required, the services of a competent professional should be sought

The advice and strategies contained herein may not be suitable for every situation. In view of ongoing research, equipment modifications, changes in governmental regulations, and the constant flow of information relating to the use of experimental reagents, equipment, and devices, the reader is urged to review and evaluate the information provided in the package insert or instructions for each chemical, piece of equipment, reagent, or device for, among other things, any changes in the instructions or indication of usage and for added warnings and precautions. The fact that an organization or Website is referred to in this work as a citation and/or a potential source of further information does not mean that the author or the publisher endorses the information the organization or Website may provide or recommendations it may make. Further, readers should be aware that Internet Websites listed in this work may have changed or disappeared between when this work was written and when it is read. No warranty may be created or extended by any promotional statements for this work. Neither the publisher nor the author shall be liable for any damages arising herefrom.

Library of Congress Cataloging-in-Publication Data

Smil, Vaclav.

Natural gas : fuel for the 21st century / Vaclav Smil. pages cm Includes bibliographical references and index. ISBN 978-1-119-01286-3 (pbk.)

1. Natural gas. 2. Gas as fuel. I. Title. TP350.S476 2015 665.7–dc23

2015017048

A catalogue record for this book is available from the British Library.

ISBN: 9781119012863

Cover image: sbayram/iStockphoto

Set in 10.5/13pt Sabon by SPi Global, Pondicherry, India

About the Author

Vaclav Smil conducts interdisciplinary research in the fields of energy, environmental and population change, food production and nutrition, technical innovation, risk assessment and public policy. He has published 35 books and close to 500 papers on these topics. He is a Distinguished Professor Emeritus at the University of Manitoba, a Fellow of the Royal Society of Canada (Science Academy) and the Member of the Order of Canada, and in 2010 he was listed by Foreign Policy among the top 50 global thinkers.

Previous works by author

China's Energy	Creating the 20th Century		
Energy in the Developing World	Transforming the 20th Century		
(edited with W. Knowland)	Energy: A Beginner's Guide		
Energy Analysis in Agriculture	Oil: A Beginner's Guide		
(with P. Nachman and T. V. Long II)	Energy in Nature and Society		
Biomass Energies	Global Catastrophes and Trends		
The Bad Earth	Why America Is Not a New Rome		
Carbon Nitrogen Sulfur	Energy Transitions		
Energy Food Environment	Energy Myths and Realities		
Energy in China's Modernization	Prime Movers of Globalization		
General Energetics	Japan's Dietary Transition and Its Impacts		
China's Environmental Crisis	(with K. Kobayashi)		
Global Ecology	Harvesting the Biosphere		
Energy in World History	Should We Eat Meat?		
Cycles of Life	Made in the USA: The Rise and Retreat		
Energies	of American Manufacturing		
Feeding the World	Making the Modern World: Materials		
Enriching the Earth	and Dematerialization		
The Earth's Biosphere	Power Density: A Key to Understanding		
Energy at the Crossroads	Energy Sources and Uses		
China's Past, China's Future			

Contents

Preface			
Acknowledgments			
Valu	able Resource with an Odd Name	1	
1.1	Methane's Advantages and Drawbacks	4	
Orig	ins and Distribution of Fossil Gases	13	
2.1	Biogenic Hydrocarbons	14	
2.2	Where to Find Natural Gas	19	
2.3	Resources and the Progression of Reserves	27	
Extr	action, Processing, Transportation, and Sales	37	
3.1	Exploration, Extraction, and Processing	40	
	3.1.1 Exploration and Drilling	41	
	3.1.2 Well Completion and Production	45	
	3.1.3 Natural Gas Processing	50	
3.2 Pipelines and Storages		54	
	3.2.1 Modern Pipelines	56	
	3.2.2 Storing Natural Gas	62	
3.3	Changing Production	65	
Nati	ural Gas as Fuel and Feedstock	71	
4.1	Industrial Uses, Heating, Cooling, and Cooking	74	
	4.1.1 Industrial Uses of Natural Gas	75	
	4.1.2 Natural Gas for Space Heating and Cooling	77	
	4.1.3 Cooking with Natural Gas	79	
	4.1.4 Liquefied Petroleum Gas	80	
	eface know Valu 1.1 Orig 2.1 2.2 2.3 Extr 3.1 3.2 3.3 Natu 4.1	eface Eknowledgments Valuable Resource with an Odd Name 1.1 Methane's Advantages and Drawbacks Origins and Distribution of Fossil Gases 2.1 Biogenic Hydrocarbons 2.2 Where to Find Natural Gas 2.3 Resources and the Progression of Reserves Extraction, Processing, Transportation, and Sales 3.1 Exploration, Extraction, and Processing 3.1.1 Exploration and Drilling 3.1.2 Well Completion and Production 3.1.3 Natural Gas Processing 3.2.1 Modern Pipelines 3.2.2 Storing Natural Gas 3.3 Changing Production Natural Gas as Fuel and Feedstock 4.1 Industrial Uses, Heating, Cooling, and Cooking 4.1.1 Industrial Uses of Natural Gas 4.1.2 Natural Gas for Space Heating and Cooling 4.1.3 Cooking with Natural Gas 4.1.4 Liquefied Petroleum Gas	

	4.2	Electricity Generation	81
		4.2.1 Gas Turbines	82
		4.2.2 CCGTs	85
	4.3	Natural Gas as a Raw Material	88
		4.3.1 Ammonia Synthesis	90
		4.3.2 Plastics from Natural Gas	95
		4.3.3 Gas-to-Liquid Conversions	98
5	Exp	orts and Emergence of Global Trade	103
	5.1	North American Natural Gas System	105
	5.2	Eurasian Networks	109
	5.3	Evolution of LNG Shipments	118
6	Dive	ersification of Sources	129
	6.1	Shale Gas	132
		6.1.1 American Shale Gas Extraction	135
		6.1.2 Shales outside the United States	140
	6.2	CBM and Tight Gas	142
		6.2.1 Tight Gas	144
	6.3	Methane Hydrates	146
7	Nat	ural Gas in Energy Transitions	151
	7.1	Fuel Substitutions and Decarbonization	
		of Energy Supply	155
	7.2	Methane in Transportation	161
		7.2.1 LNG	162
		7.2.2 CNG	166
	7.3	Natural Gas and the Environment	168
		7.3.1 Methane Emissions from Gas Industry	169
		7.3.2 Methane from Shale Gas	175
		7.3.3 Water Use and Contamination	180
8	The	Best Fuel for the Twenty-First Century?	189
	8.1	How Far Will Gas Go?	192
	8.2	Shale Gas Prospects	199
	8.3	Global LNG	208
	8.4	Uncertain Futures	214
Re	eferen	ces	221
Ine	dex		245

Preface

This book, my 36th, has an unusual origin. For decades, I have followed an unvarying pattern: as I am finishing a book, I had already chosen a new project from a few ideas that had been queuing in my mind, sometimes coming to the fore just in a matter of months and in two exceptional cases (books on creating and transforming the twentieth century) after a wait of nearly two decades. But in January 2014, as I was about to complete the first draft of my latest book (*Power Density: A Key to Understanding Energy Sources and Uses*), I was still undecided what to do next. Then I got an e-mail from Nick Schulz at ExxonMobil who is also a reader (and a reviewer) of my books, asking me if I had considered writing a book about natural gas akin to my two beginner's guides (to energy and to oil) published by Oneworld in Oxford in, respectively, 2006 and 2008.

I had written about natural gas in most of my energy books, but in January 2014, the idea of a book solely devoted to it was not even at the end of my mental book queue. But considering all the attention natural gas has been getting, it immediately seemed an obvious thing to do. And because there are so many components and perspectives to the natural gas story—ranging from the fuel as a key part of the United States' much publicized energy revolution to its strategic value in Russia's in its dealings with Europe and to its role in replacing coal in the quest for reduced greenhouse gas emissions—it was no less obvious that I will have to approach the task in my usual interdisciplinary fashion and that I will dwell not only with what we know but also describe and appraise many unknowns and uncertainties that will affect the fuel's importance in the twenty-first century.

I began to write this natural gas book on March 1, 2014, intent on replicating approach and coverage of the two beginner's guides: the

intended readers being reasonably well educated (but not energy experts) and the coverage extending to all major relevant topics (be they geological, technical, economical, or environmental). But as the writing proceeded, I decided to depart from that course because I realized that some of the recent claims and controversies concerning natural gas require more detailed examinations. That is why the book is thoroughly referenced (the two guides had only short lists of suggested readings at the end), why it is significantly more quantitative and longer than the two guides, and why I dropped the word *primer* from its initial subtitle.

To many forward-looking energy experts, this may seem to be a strangely retrograde book. They would ask why dwell on the resources, extraction, and uses of a fossil fuel and why extol its advantages at a time when renewable fuels and decentralized electricity generation converting solar radiation and wind are poised to take over the global energy supply. That may be a fashionable narrative—but it is wrong, and there will be no rapid takeover by the new renewables. We are a fossilfueled civilization, and we will continue to be one for decades to come as the pace of grand energy transition to new forms of energy is inherently slow. In 1990, the world derived 88% of its primary commercial energy (leaving aside noncommercial wood and crop residues burned mostly by rural families in low-income nations) from fossil fuels; in 2012, the rate was still almost 87%, with renewables supplying 8.6%, but most of that has been hydroelectricity and new renewables (wind, solar, geothermal, biofuels) provided just 1.9%; and in 2013, their share rose to nearly 2.2% (Smil, 2014; BP, 2014a).

Share of new renewables in the global commercial primary energy supply will keep on increasing, but a more consequential energy transition of the coming decades will be from coal and crude oil to natural gas. With this book, I hope to provide a solid background for appreciating its importance, its limits, and a multitude of its impacts. This goal dictated the book's broad coverage where findings from a number of disciplines (geochemistry, geology, chemistry, physics, environmental science, economics, history) and process descriptions from relevant engineering practices (hydrocarbon exploration, drilling, and production; gas processing; pipeline transportation; gas combustion in boilers and engines; gas liquefaction and shipping) are combined to provide a relatively thorough understanding of requirements, benefits, and challenges of natural gas ascendance.

Acknowledgments

Thanks to Nick Schulz for starting the process (see the Preface).

Thanks to two Sarahs—Sarah Higginbotham and Sarah Keegan—at John Wiley for guiding the book to its publication.

Thanks again to the Seattle team—Wendy Quesinberry, Jinna Hagerty, Ian Saunders, Leah Bernstein, and Anu Horsman—for their meticulous effort with which they prepared images, gathered photographs, secured needed permissions, and created original illustrations, that are reproduced in this book.

1 Valuable Resource with an Odd Name

Natural gas, one of three fossil fuels that energize modern economies, has an oddly indiscriminate name. Nature is, after all, full of gases, some present in enormous volumes, others only in trace quantities. Nitrogen (78.08%) and oxygen (20.94%) make up all but 1% of dry atmosphere's volume, the rest being constant amounts of rare gases (mainly argon, neon, and krypton altogether about 0.94%) and slowly rising levels of carbon dioxide (CO₂). The increase of this greenhouse gas has been caused by rising anthropogenic emissions from combustion of fossil fuels and land use changes (mainly tropical deforestation), and CO₂ concentrations have now surpassed 0.04% by volume, or 400 parts per million (ppm), about 40% higher than the preindustrial level (CDIAC, 2014).

In addition, the atmosphere contains variable concentrations of water vapor and trace gases originating from natural (abiogenic and biogenic) processes and from human activities. Their long list includes nitrogen oxides (NO, NO₂, N₂O) from combustion (be it of fossil fuels, fuel wood, or emissions from forest and grassland fires), lightning, and bacterial metabolism; sulfur oxides (SO₂ and SO₃) mainly from the combustion of coal and liquid hydrocarbons, nonferrous metallurgy, and also volcanic eruptions; hydrogen sulfide (H₂S) from anaerobic decomposition and from volcanoes; ammonia (NH₃) from livestock and from volatilization of organic and inorganic fertilizers; and dimethyl sulfide (C₂H₆S) from metabolism of marine algae.

Natural Gas: Fuel for the 21st Century, First Edition. Vaclav Smil.

© 2015 John Wiley & Sons, Ltd. Published 2015 by John Wiley & Sons, Ltd.

But the gas whose atmospheric presence constitutes the greatest departure from a steady-state composition that would result from the absence of life on the Earth is methane (CH₄), the simplest of all hydrocarbons, whose molecules are composed only of hydrogen and carbon atoms. Methane is produced during strictly anaerobic decomposition of organic matter by species of archaea, with *Methanobacter*, *Methanococcus*, *Methanosarcina*, and *Methanothermobacter* being the major methanogenic genera. Although the gas occupies a mere 0.000179% of the atmosphere by volume (1.79 ppm), that presence is 29 orders of magnitude higher than it would be on a lifeless Earth (Lovelock and Margulis, 1974). The second highest disequilibrium attributable to life on the Earth is 27 orders of magnitude for NH₃.

Methanogens residing in anaerobic environments (mainly in wetlands) have been releasing CH_4 for more than three billion years. As with other metabolic processes, their activity is temperature dependent, and this dependence (across microbial to ecosystem scales) is considerably higher than has been previously observed for either photosynthesis or respiration (Yvon-Durocher et al., 2014). Methanogenesis rises 57-fold as temperature increases from 0 to 30°C, and the increasing CH_4 : CO_2 ratio may have important consequences for future positive feedbacks between global warming and changes in carbon cycle.

Free-living methanogens were eventually joined by archaea that are residing in the digestive tract (in enlarged hindgut compartments) of four arthropod orders, in millipedes, termites, cockroaches, and scarab beetles (Brune, 2010), with the tropical termites being the most common invertebrate CH₄ emitters. Although most vertebrates also emit CH₄ (it comes from intestinal anaerobic protozoa that harbor endosymbiotic methanogens), their contributions appear to have a bimodal distribution and are not determined by diet. Only a few animals are intermediate methane producers, while less than half of the studied taxa (including insectivorous bats and herbivorous pandas) produce almost no CH₄, while primates belong to the group of high emitters, as do elephants, horses, and crocodiles.

But by far the largest contribution comes from ruminant species, from cattle, sheep, and goats (Hackstein and van Alen, 2010). Soil-dwelling methanotrophs and atmospheric oxidation that produces H_2O and CO_2 have been methane's major biospheric sinks, and in the absence of any anthropogenic emissions, atmospheric concentrations of CH_4 would have remained in a fairly stable disequilibrium. These emissions began millennia before we began to exploit natural gas as a fuel: atmospheric concentration of CH_4 began to rise first with the expansion of wet-field (rice) cropping in Asia (Ruddiman, 2005; Figure 1.1).



Figure 1.1 Methanogens in rice fields (here in terraced plantings in China's Yunnan) are a large source of CH₄. Reproduced from http://upload.wikimedia.org/wikipedia/commons/7/70/Terrace_field_yunnan_china_denoised.jpg. © Wikipedia Commons.

Existence of inflammable gas emanating from wetlands and bubbling up from lake bottoms was known for centuries, and the phenomenon was noted by such famous eighteenth-century investigators of natural processes as Benjamin Franklin, Joseph Priestley, and Alessandro Volta. In 1777, after observing gas bubbles in Lago di Maggiore, Alessandro Volta published *Lettere sull' Aria inflammabile native delle Paludi*, a slim book about "native inflammable air of marshlands" (Volta, 1777). Two years later, Volta isolated methane, the simplest hydrocarbon molecule and the first in the series of compounds following the general formula of C_nH_{2n+2} . When in 1866 August Wilhelm von Hofmann proposed a systematic nomenclature of hydrocarbons, that series became known as alkanes (alkenes are C_nH_{2n} ; alkines are C_nH_{2n-2}).

The second compound in the alkane series is ethane (C_2H_6), and the third one is propane (C_3H_8). The fossil fuel that became known as natural gas and that is present in different formations in the topmost layers of the Earth's crust is usually a mixture of these three simplest alkanes, with methane always dominant (sometimes more than 95% by weight) and only exceptionally with less than 75% of the total mass (Speight, 2007). C_2H_6 makes up mostly between 2 and 7% and C_3H_8 typically just 0.1–1.3%. Heavier homologs—mainly butane (C_4H_{10}) and pentane (C_5H_{12})—are also often present. All C_2 - C_5 compounds (and sometimes even traces of heavier homologs) are classed as natural gas liquids (NGL), while propane and butane are often combined and marketed (in pressurized containers) as liquid petroleum gases (LPG).

Most natural gases also contain small amounts of CO_2 , H_2S , nitrogen, helium, and water vapor, but their composition becomes more uniform before they are sent from production sites to customers. In order to prevent condensation and corrosion in pipelines, gas processing plants remove all heavier alkanes: these compounds liquefy once they reach the surface and are marketed separately as NGL, mostly as valuable feedstocks for petrochemical industry, some also as portable fuels. Natural gas processing also removes H_2S , CO_2 , and water vapor and (if they are present) N_2 and He (for details, see Chapter 3).

1.1 METHANE'S ADVANTAGES AND DRAWBACKS

No energy source is perfect when judged by multiple criteria that fully appraise its value and its impacts. For fuels, the list must include not only energy density, transportability, storability, and combustion efficiency but also convenience, cleanliness, and flexibility of use; contribution to the generation of greenhouse gases; and reliability and durability of supply. When compared to its three principal fuel alternatives—wood, coal, and liquids derived from crude oil—natural gas scores poorly only on the first criterion: at ambient pressure and temperature, its specific density, and hence its energy density, is obviously lower than that of solids or liquids. On all other criteria, natural gas scores no less than very good, and on most of them, it is excellent or superior.

Specific density of methane is 0.718 kg/m^3 (0.718 g/l) at 0° C and 0.656 g/l at 25° C or about 55% of air's density (1.184 kg/m^3 at 25° C). Specific densities of common liquid fuels are almost exactly, 1,000 times higher, with gasoline at 745 kg/m^3 and diesel fuel at 840 kg/m^3 , while coal densities of bituminous coals range from 1,200 to 1,400 kg/m³. Only when methane is liquefied (by lowering its temperature to -162° C) does its specific density reach the same order of magnitude as in liquid fuels (428 kg/m^3), and it is equal to specific density of many (particularly coniferous) wood species, including firs, cedars, spruces, and pines.

Energy density can refer to the lower heating value (LHV) or higher heating value (HHV); the former rate assumes that the latent heat of vaporization of water produced during the combustion is not recovered, and hence it is lower than HHV that accounts for the latent heat of

water vaporization. Volumetric values for methane are 37.7 MJ/m³ for HHV and 33.9 MJ/m³ for LHV (10% difference), while the actual HHVs for natural gases range between 33.3 MJ/m³ for the Dutch gas from Groningen to about 42 MJ/m³ for the Algerian gas from Hasi R'Mel. Again, these values are three orders of magnitude lower than the volumetric energy density of liquid fuels: gasoline's HHV is 35 GJ/m³ and diesel oil rates nearly 36.5 GJ/m³. Liquefied natural gas (50 MJ/kg and 0.428 kg/l) has volumetric energy density of about 21.4 GJ/m³ or roughly 600 times the value for typical natural gas containing 35–36 MJ/m³.

Methane's low energy density is no obstacle to high-volume, low-cost, long-distance terrestrial transport. There is, of course, substantial initial capital cost of pipeline construction (including a requisite number of compression stations), and energy needed to power reciprocating engines, gas turbines, or electric motors is the main operating expenditure. But as long as the lines and the compressors are properly engineered, there is no practical limit to distances that can be spanned: multiple lines bring natural gas from supergiant fields of Western Siberia to Western Europe, more than 5000km to the west. Main trunk of China's West-East pipeline from Khorgas (Xinjiang) to Guangzhou is over 4,800km long, and eight major branches add up to the total length of 9,100 km (China.org, 2014). Moreover, pipelines transport gas at very low cost per unit of delivered energy and can do so on scales an order of magnitude higher than the transmission of electricity where technical consideration limit the maxima to 2-3 GW for single lines, while gas pipelines can have capacities of 10–25 GW (IGU, 2012).

Undersea pipelines are now a proven technical option in shallow waters: two parallel 1,224 km long lines of the Nord Stream project built between 2010 and 2012 between Russia and Germany (from Vyborg, just north of Sankt Petersburg to Lubmin near Greifswald in Mecklenburg-Vorpommern) to transport 55 Gm³/year were laid deliberately in the Baltic seabed in order to avoid crossing Ukraine or Belarus before reaching the EU (Nord Stream, 2014). Crossing deep seas is another matter: low energy density of natural gas precludes any possibility of shipborne exports at atmospheric pressure, and the only economic option for intercontinental shipments is to liquefy the gas and carry it in insulated containers on purpose-built tankers; this technique, still much more expensive than pipeline transportation, will be appraised in detail in Chapter 5. Methane's low energy density is also a disadvantage when using the fuel in road vehicles, and once again, the only way to make these uses economical is by compression or liquefaction of the gas (for details, see Chapter 7).

Low energy density would be a challenge if the only **storage** option would be as uncompressed gas in aboveground tanks: even a giant tank with 100 m in diameter and 100 m tall (containing about 785,000 m³ or roughly 28 TJ) would store gas for heating only 500 homes during a typical midcontinental Canadian winter. Obviously, volumes of accessible stores must be many orders of magnitude higher, high enough to carry large midlatitude cities through long winters. The easiest, and the most common, choice is to store the fuel by injecting it into depleted natural gas reservoirs; other options are storage in aquifers (in porous, permeable rocks) and (on a much smaller scale but with almost perfect sealing) in salt caverns.

High **combustion efficiency** is the result of high temperatures achievable when burning the gas in large boilers and, better yet, in gas turbines. Gas turbines are now the single most efficient fuel convertors on the market and that high performance can be further boosted by combining them with steam turbines. When exiting a gas turbine, the exhaust has temperature of 480–600°C, and it can be used to vaporize water, and the resulting steam runs an attached steam turbine (Kehlhofer, Rukes, and Hannemann, 2009). Such combined cycle generation (CCG, or combined cycle power plants, CCPP) can achieve overall efficiency of about 60%, the rate unsurpassed by any other mode of fuel combustion (Figure 1.2). And modern natural gas-fired furnaces used to heat North America's houses leave almost no room for improvement as they convert 95–97% of incoming gas to heat that is forced by a fan through ducting and floor registers into rooms.

Little needs to be said about the **convenience of use**. The only chore an occupant has to do in houses heated by natural gas is to set a thermostat to desired levels (with programmable thermostats, this can be done accurately with specific day/night or weekday/weekend variations)—and make sure that the furnace is checked and cleaned once a year. Electronic ignition, now standard on furnaces as well as on cooking stoves, has eliminated wasteful pilot lights, and auto reignition makes the switching a one-step operation (turning a knob to desired intensity) instead (as is the case with standard electronic ignition) of turning a knob to on position (to open a gas valve), waiting a second for ignition, and then turning a knob to a preferred flame intensity.

Combination of these desirable attributes—safe and reliable delivery by pipelines from fields and voluminous storages, automatic dispensation of the fuel by electronically controlled furnaces, effortless control of temperature settings for furnaces and stoves, and low environmental impact—means that natural gas is an excellent source of energy for



Figure 1.2 Combined cycle gas turbine: energy flow and a model of GE installation. Reproduced courtesy of General Electric Company.

densely populated cities that will house most of the world's population in the twenty-first century. As Ausubel (2003, 2) put it, "the strongly preferred configuration for very dense spatial consumption of energy is a grid that can be fed and bled continuously at variable rates"—and besides electricity, natural gas is the only energy source that can be distributed by such a grid and used directly in that way.

As for the **cleanliness of use**, electricity is the only competitor at the point of final consumption. Combustion of pure methane, or a mixture

of methane and ethane, produces only water and carbon dioxide $(CH_4 + O_2 \rightarrow H_2O + CO_2)$. There are no emissions of acidifying sulfur oxides (as already noted, H₂S is stripped from natural gas before it is sent through pipelines), while heating houses with coal or fuel oil generates often fairly high emissions of SO₂. Moreover, coal combustion produces high concentrations of particulate matter (diameters of <10 µm, PM₁₀), and the smallest particles (diameter <2.5 µm, PM_{2.5}) are also fairly abundant when burning heavier liquids, while combustion of natural gas emits only a small fraction of the finest particulate matter compared to the burning of solid or liquid fuels.

Similarly, natural gas is a superior choice when generating electricity in large power plants. Coal burning in large central stations remains a globally dominant way of thermal electricity generation, and even with appropriate modern air pollution controls (electrostatic precipitators to capture more than 99% of fly ash produced by the combustion of finely pulverized coal in boilers; flue gas desulfurization to remove more than 80% of SO₂ produced by oxidation of coal's organic and inorganic sulfur), to generate a unit of electricity, it releases five to six times more PM_{2.5} and PM₁₀ and in many cases more than 1,000 times as much SO₂ as does the combustion of natural gas (TNO, 2007).

No other form of energy has a higher **flexibility of use** than electricity: commercial flying is the only common final conversion that it cannot support, as it can be used for heating, lighting, cooking, and refrigeration; for supplying processing heat in many industries, powering all electronic gadgets and all stationary machinery; for propelling vehicles, trains, and ships; and for producing metals (electric arc furnaces and electrochemical processes). Natural gas shares the flying limitation with electricity—but otherwise, the fuel is remarkably flexible as its common uses range from household space heating and cooking to peak electricity generation and from powering compressors in nitrogen fertilizer plants to propelling LNG tankers (for details, see Chapter 4).

Because climate change and the future extent of global warming have become major concerns of public policy, **contribution to the generation of greenhouse gases** has emerged as a key criterion to assess desirability of fuels. On this score, natural gas remains unsurpassed as its combustion generates less CO_2 per unit of useful energy than does the burning of coal, liquid fuels, or common biofuels (wood, charcoal, crop residues). In terms of kg CO_2/GJ , the descending rates are approximately 110 for solid biofuels, 95 for coal, 77 for heavy fuel oil, 75 for diesel, 70 for gasoline, and 56 for natural gas (Climate Registry, 2013). Moreover, high-temperature coal combustion in large power stations also produces much higher volumes of the other two most important greenhouse gases: more than 10 times as much CH_4 and more than 20 times as much N_2O per unit of generated electricity (details in Chapter 7).

Reliability of supply is perhaps best demonstrated by the fact that inhabitants of large northern cities hardly ever think about having their gas supply interrupted because such experiences are exceedingly rare. There may be a temporary problem with a distribution line bringing the gas to a house, and there are rare—and in a great majority of cases perfectly preventable—explosions. A widely reported explosion that leveled two apartment buildings, killed 7, and injured more than 60 in New York's East Harlem on March 12, 2014, is a good illustration of such an avoidable accident. Several residents said that they "smelled gas in the area for several days" (Slattery and Hutchinson, 2014). That unmistakable smell is butanethiol (butyl mercaptan, $C_4H_{10}S$) that is added to odorless natural gas in order to detect even tiny leaks by smell (humans can detect as little as 10 parts per billion of the skunk-like odor).

Nor are there any great uncertainties about the reliability of international gas supply. The most notable case of interrupted supply took place in January 2009 when Gazprom cut off all flows of Russian gas to Ukraine (also affecting the deliveries to more than half a dozen European countries whose gas must flow through the Ukrainian lines) due to the unpaid accumulated debt for previous deliveries (Daly, 2009). The flow was restored after 13 days, but by March 2014, new Ukrainian debts threatened a reprise of 2009, although Gazprom maintained that the EU consumers west of the Ukraine would not be affected. Another threat of export interruption (following Russia's annexation of Crimea and fighting in the Eastern Ukraine) was averted by a deal conclude in late October 2014. But this unique, albeit recurrent, threat is not a reflection of general natural gas trading practices, rather an exception due to an unsettled nature of Russia's relations with its neighbors in the post-Soviet era.

Durability of supply is, of course, the function of resources in place and of our technical and managerial capabilities to translate their substantial part into economically recoverable commodities—and natural gas ranks high on all of these accounts. Natural gas is present in abundance in the topmost crust in several formations, but until recently, only three kinds of gaseous hydrocarbons dominated commercial production. They are natural gases associated with crude oils, a very common occurrence in nearly all of the world's major oil reservoirs; these gases may be present in separate layers in a reservoir containing oil and gas, they may accumulate on top of oil as gas caps, or they may be (another common occurrence) dissolved in crude oil. Usual cutoff for associated gas is when a gas/oil ratio is less than $20,000 \text{ ft}^3$ per barrel (in SI units about 350 m^3 of gas per 100 l of oil).

In contrast, nonassociated natural gas comes from gas fields, that is, from hydrocarbon reservoirs whose gas/oil ratio exceeds the rate noted in the preceding paragraph. The two common categories of nonassociated natural gas are wet (also called rich) gas that is extracted from reservoirs where methane dominates but where heavier alkanes (NGL) account for a substantial share of hydrocarbon mixtures, while dry natural gas comes from reservoirs where prolonged heat processing produced gas mixtures containing more than 90% or even more than 95% of methane and only small amounts of ethane and other alkanes.

These three conventional resources continue to dominate global extraction of natural gas, but some countries and regions are now producing increasing quantities of gaseous fuel from coal beds and from shales, while extraction of gas from methane hydrates still awaits additional technical advances before becoming commercial. All resource totals are always only temporary best estimates, but in this instance, their magnitude guarantees generations of future use: the best recent assessments of recoverable resources indicate that the global peak of natural gas extraction is most likely no closer than around 2050 or perhaps even after 2070. Another reassuring perspective shows that during the past three decades (between 1982 and 2012), the world gas consumption rose 2.3-fold, but the global reserve/production ratio has remained fairly constant, fluctuating within a narrowband of 55–65 years and not signaling any imminent radical shifts.

This brief review shows that natural gas is an exceptional source of primary energy for all modern economies—not only because it combines a number of practical advantages and benefits but also because it either fits existing infrastructures or because any further expansion of extraction, transportation, and use can rely on proven and economical technical and managerial arrangements. This book will offer a concise, but systematic, review of key aspects that define and delimit the fuel's great potential during the twenty-first century: its biogenic origins, crustal concentrations, and widespread distribution; its exploration, extraction, processing, and pipeline transportation; its common uses for heat and electricity generation and as a key feedstock for many chemical syntheses; its pipeline and intercontinental exports and the emergence of global trade; diversification of its commercial sources; and the fuel's role in energy transitions and environmental consequences of its combustion.

VALUABLE RESOURCE WITH AN ODD NAME

Given the scope of the coverage and the length of the text, it is easy to appreciate that writing this book was a serial exercise in exclusion; at the same time and with every key topic, I have tried to go sufficiently below the shallows that now dominate the (web page-like) writings about technical, environmental, and economic complexities for nonexperts. That is why I hope that those readers who will persevere (and tolerate what I always think of as a necessary leavening by many requisite numbers) will be rewarded by acquiring a good basis for an unbiased and deeper understanding of a critical segment of modern energy use and of its increasing importance.

2 Origins and Distribution of Fossil Gases

Many gases encountered in the biosphere are of organic (biogenic) origin: as already explained in the previous chapter, methane is actually the best example of a gas whose concentration is orders of magnitude higher than it would be on a lifeless Earth. Other gases generated by microbial metabolism include hydrogen (H₂), hydrogen sulfide (H₂S), carbon monoxide and dioxide (CO and CO₂), nitric oxide (NO), nitrous oxide (N₂O), and ammonia (NH₃), while photosynthesis releases huge volumes of oxygen (O₂), and all animal metabolism emits CO₂. But many of these gases are also of inorganic origins: CO from incomplete combustion of fuels and CO, H₂S, and SO₂ from volcanic eruptions—and methane was found in hydrothermal vents at the bottom of the Pacific Ocean and in other crustal fluids.

Given these realities, we have to ask if all fossil methane, or at least an overwhelming majority of its presence in the crust's topmost layer, is of biogenic origin (arising from transformation of organic matter) or if a significant share of it (if not most of it) is abiogenic, arising from processes that have not required metabolism of living organisms. These obvious questions have been asked and answered: debates about the origin of natural gas have been a part of a wider inquiry about the genesis of fossil hydrocarbons, with the consensus coming on the side of their organic provenance and with dissenters arguing that inorganic process is a better way to explain the genesis of vast gas volumes in the Earth's upper crust.

Natural Gas: Fuel for the 21st Century, First Edition. Vaclav Smil.

^{© 2015} John Wiley & Sons, Ltd. Published 2015 by John Wiley & Sons, Ltd.