



Universität Stuttgart  
Institut für Strahlwerkzeuge



## LASER IN DER MATERIALBEARBEITUNG

Forschungsberichte des IFSW

Martin Rumpel

### **Applications of Grating Waveguide Structures in Solid-State Lasers**

utzverlag



Martin Rumpel

**Applications of Grating Waveguide Structures in  
Solid-State Lasers**

utzverlag · München 2019

Laser in der Materialbearbeitung  
Band 95

Ebook (PDF)-Ausgabe:  
ISBN 978-3-8316-7479-4 Version: 1 vom 27.06.2019  
Copyright© utzverlag 2019

Alternative Ausgabe: Softcover  
ISBN 978-3-8316-4801-6  
Copyright© utzverlag 2019

Laser in der Materialbearbeitung  
Forschungsberichte des IFSW

M. Rumpel  
Applications of Grating Waveguide  
Structures in Solid-State Lasers

# **Laser in der Materialbearbeitung**

## **Forschungsberichte des IFSW**

Herausgegeben von

Prof. Dr. phil. nat. Thomas Graf, Universität Stuttgart  
Institut für Strahlwerkzeuge (IFSW)

Das Strahlwerkzeug Laser gewinnt zunehmende Bedeutung für die industrielle Fertigung. Einhergehend mit seiner Akzeptanz und Verbreitung wachsen die Anforderungen bezüglich Effizienz und Qualität an die Geräte selbst wie auch an die Bearbeitungsprozesse. Gleichzeitig werden immer neue Anwendungsfelder erschlossen. In diesem Zusammenhang auftretende wissenschaftliche und technische Problemstellungen können nur in partnerschaftlicher Zusammenarbeit zwischen Industrie und Forschungsinstituten bewältigt werden.

Das 1986 gegründete Institut für Strahlwerkzeuge der Universität Stuttgart (IFSW) beschäftigt sich unter verschiedenen Aspekten und in vielfältiger Form mit dem Laser als einem Werkzeug. Wesentliche Schwerpunkte bilden die Weiterentwicklung von Strahlquellen, optischen Elementen zur Strahlführung und Strahlformung, Komponenten zur Prozessdurchführung und die Optimierung der Bearbeitungsverfahren. Die Arbeiten umfassen den Bereich von physikalischen Grundlagen über anwendungsorientierte Aufgabenstellungen bis hin zu praxisnaher Auftragsforschung.

Die Buchreihe „Laser in der Materialbearbeitung – Forschungsberichte des IFSW“ soll einen in der Industrie wie in Forschungsinstituten tätigen Interessentenkreis über abgeschlossene Forschungsarbeiten, Themenschwerpunkte und Dissertationen informieren. Studenten soll die Möglichkeit der Wissensvertiefung gegeben werden.

# **Applications of Grating Waveguide Structures in Solid-State Lasers**

von Dr.-Ing. Martin Rumpel  
Universität Stuttgart



utzverlag München

Als Dissertation genehmigt  
von der Fakultät für Konstruktions-, Produktions- und Fahrzeugtechnik  
der Universität Stuttgart

Hauptberichter: Prof. Dr. phil. nat. Thomas Graf  
Mitberichter: Prof. Dr. rer. nat. Thomas Dekorsy

Bibliografische Information der Deutschen Nationalbibliothek  
Die Deutsche Nationalbibliothek verzeichnet diese Publikation  
in der Deutschen Nationalbibliografie; detaillierte bibliografische  
Daten sind im Internet über <http://dnb.ddb.de> abrufbar.

Zugleich: Dissertation, Stuttgart, Univ., 2019

D 93

Das Werk ist urheberrechtlich geschützt.  
Sämtliche, auch auszugsweise Verwertungen bleiben vorbehalten.

Copyright © utzverlag GmbH 2019

ISBN 978-3-8316-4801-6

Printed in Germany

utzverlag GmbH, München  
Tel.: 089-277791-00 · [www.utzverlag.de](http://www.utzverlag.de)

# Content

List of figures.....	7
List of tables.....	11
Symbols and abbreviations.....	13
Extended abstract.....	15
Kurzfassung in deutscher Sprache.....	17
1 Introduction.....	21
1.1 Motivation.....	21
1.2 State of the art.....	22
1.2.1 Wavelength and polarization stabilization in TDL.....	22
1.2.2 Fully-dielectric diffraction gratings.....	23
2 Objective of the thesis.....	25
2.1 Structure of this work.....	25
2.2 Unique properties of GWS for applications in laser physics.....	25
3 Introduction to GWS.....	33
3.1 Historical origin.....	33
3.1.1 Resonant-Reflection GWS.....	33
3.1.2 Resonant-Diffraction GWS.....	34
3.1.3 Leaky-Mode GWS.....	35
3.2 Physical mechanisms in GWS.....	36
3.2.1 Guided and leaky modes in planar waveguides.....	36
3.2.2 Diffraction gratings.....	38
3.2.3 Diffraction grating assisted coupling of planar waveguide modes.....	40
3.2.4 Resonant Reflection.....	41
3.2.5 Resonant Diffraction.....	44
3.2.6 Leaky-mode excitation.....	47
3.3 Design of GWS for applications in lasers.....	49
3.3.1 Resonant-Reflection GWS.....	50
3.3.1.1 Single-layer waveguide.....	50
3.3.1.2 Single-layer waveguide with partial reflector.....	50
3.3.1.3 Special considerations for application as OC.....	53

---

3.3.2	Resonant-Diffraction GWS .....	53
3.3.2.1	Design for Littrow-configuration .....	53
3.3.2.2	Obtaining a high LIDT .....	56
3.3.3	Leaky-Mode GWS .....	57
3.3.3.1	Application as end-mirror.....	57
3.3.3.2	Application as OC.....	57
4	Experimental results.....	61
4.1	Intra-cavity stabilization of linear polarization and emission wavelength.....	61
4.1.1	RR-GWS as cavity end-mirror.....	61
4.1.2	RR-GWS as folding-mirror.....	64
4.1.2.1	In an Er:YAG rod-laser .....	64
4.1.2.2	In an Yb:YAG TDL.....	64
4.1.3	RD-GWS as cavity end-mirror.....	66
4.1.4	RD-GWS as OC .....	67
4.2	Generation of radiation with azimuthal polarization.....	70
4.2.1	RR-GWS as cavity end-mirror .....	71
4.2.2	LM-GWS as cavity end-mirror .....	73
4.3	Wavelength tuning .....	75
4.3.1	By using RR-GWS.....	75
4.3.2	By using RD-GWS.....	77
4.4	Intra-cavity SHG .....	77
4.4.1	Spectroscopic characterization of RD-GWS.....	78
4.4.2	Intra-cavity SHG experiment .....	79
4.5	Stretching and compression of laser pulses .....	80
4.5.1	Intra-cavity laser pulse stretching .....	81
4.5.2	Extra-cavity laser pulse compression.....	81
4.6	Manufacturing tolerances.....	81
4.6.1	Investigations on the grating profile in the coating layers .....	82
4.6.2	Subsequent etching to shape the spectral profile of the DE.....	84
5	Summary and outlook .....	87
	Bibliography.....	91
	Danksagung.....	101

# List of figures

*Figure 1: Exemplary arrangements of substrate, dielectric coating layers, and linear grating to exploit the three different phenomena as discussed in this thesis. Light colors represent low values of refractive indices and dark colors represent high values of refractive indices in each GWS. .... 26*

*Figure 2: Example for the spectral reflectivity of a single-layer RR-GWS [Vog12], used at normal incidence (a), and a multi-layer GWS [Rum13] used at tilted incidence (b). .... 28*

*Figure 3: Example of the spectral DE in the -1<sup>st</sup> diffraction order of a RD-GWS [Rum12, Die15, Pie16], used in the Littrow-configuration (a) and with a separation between incident and diffracted beam [Rum14] (b). .... 29*

*Figure 4: Exemplary spectral reflectivity of a LM GWS for the use as a polarizing end-mirror in a resonator [Rum12-2] (a) or as the OC of the resonator [Eck16] (b). .... 30*

*Figure 5: Planer optical waveguide, comprising J uniform layers of refractive index  $n_j$  and thickness  $w_j$  (a) and field orientation for s- and p-polarization (b) as e.g. introduced in [Ada81]. .... 37*

*Figure 6: Properties of diffraction gratings: diffraction orders generated in reflection (R) and transmission (T) (a), definition of the polarization for linear and circular gratings in (b) and (c). The roman numbers denote the quadrants referred to in the text. .... 38*

*Figure 7: Visualization of the mode excitation in the reciprocal space. .... 41*

*Figure 8: Ray-optics model of the guided-mode resonance according to [Ros97] for the single-layer RR-GWS of [Vog12]. The spectral reflectivity for radiation with TE and TM polarization of a GWS of this architecture is shown in Figure 2, a). .... 42*

*Figure 9: Simulated distribution of the field for TE polarization of the RR-GWS of [Vog12] at  $AOI = 0^\circ$  and  $\lambda = 1030$  nm (a) and the RR-GWS of [Aub14] at  $AOI = -23.89^\circ$  and  $\lambda = 1617$  nm (b). .... 44*

*Figure 10: Schematic of the RD-GWS with mechanisms leading to the resonant diffraction. .... 46*

*Figure 11: Simulated distribution of the field for TE polarization of the LM-GWS from [Rum12] in the Littrow-configuration. .... 47*

*Figure 12: a) no leaky mode excitation for TE polarization and b), leaky mode excitation for TM polarization of the LM-GWS of [Rum12-2] at 1030 nm wavelength and normal incidence. .... 48*

<i>Figure 13: Comparison of single-layer RR-GWS from [Vog12] to multi-layer designs (see text for the nomenclature) from [Rum13].</i> .....	52
<i>Figure 14: Simulated distribution of the field for TE polarization in the 5-30-9.8975 GWS of [Rum13] at resonance.</i> .....	53
<i>Figure 15: DE versus wavelength for a fixed AOI (red) and in Littrow-configuration (brown) for the RD-GWS of [Rum12]. The blue curves show the result of the design optimization as described in the text.</i> .....	54
<i>Figure 16: Diffraction efficiency in Littrow-configuration for GWS#1 from [Rum12] (a) and GWS#2 from [Die15, Pie16] (b). The brown, orange, and blue areas indicate a DE &gt; 99.7%, <math>\geq 99\%</math>, and &lt; 99%, respectively, between <math>\lambda = 1028 \dots 1034</math> nm in the -1<sup>st</sup> diffraction order and for TE polarized radiation.</i> .....	55
<i>Figure 17: Spectral reflectivity (R) and transmission (T) for the 0<sup>th</sup> and -1<sup>th</sup> diffraction orders of the LM-GWS used as polarizing OC.</i> .....	59
<i>Figure 18: Coating sequence of 18 alternating layers for the LM-GWS used as OC. The first two layers are detuned from the quarter-wave condition to optimize the modal content of the GWS.</i> .....	59
<i>Figure 19: Resonator of the Yb:YAG TDL as reported on in [Vog12].</i> .....	62
<i>Figure 20: Output power and optical efficiency versus power density incident on the GWS (a), spectra of emitted beams with and without GWS (b).</i> .....	63
<i>Figure 21: Resonator of TDL as reported on in [Rum13].</i> .....	65
<i>Figure 22: Emission bandwidth and GWS surface temperature for the TDL with a HR end-mirror or the RD-GWS (a), spectra of emitted beams at 287 W of pumping power (b).</i> .....	67
<i>Figure 23: Measurement and simulation of the diffraction spectrum for a RD-GWS in Littrow-configuration.</i> .....	68
<i>Figure 24: Resonator of the TDL as reported on in [Rum12].</i> .....	69
<i>Figure 25: Power curves and optical efficiency at 615 W of pumping power when using the RD-GWS as end-mirror of the cavity of the OC.</i> .....	70
<i>Figure 26: Resonator of TDL as reported on in [Rum12-2].</i> .....	71
<i>Figure 27: Intensity distribution of the output beam with an azimuthal state of polarization and 93 W of power, obtained by using the RR-GWS in the cavity of a TDL as the end-mirror. In order to visualize the state of polarization, a rotating polarization analyzer was placed into the beam with various orientations of its transmission axis.</i> .....	72

- Figure 28: Measured and simulated reflectivity spectrum of [Rum12-2] (a) and spectrum of emitted beams with either RR-GWS or HR end-mirror in the cavity (b).. 73
- Figure 29: Intensity distribution of the output beam with azimuthal state of polarization and 103 W of power, obtained by using the LM-GWS in the cavity of a TDL as polarizing end-mirror. In order to visualize the state of polarization, a rotating polarization analyzer was placed into the beam with various orientations of its transmission axis. .... 74
- Figure 30: Measured spectra of the emitted beams with the LM-GWS or the HR end-mirror in the cavity. .... 74
- Figure 31: Wavelength tuning in an Yb:YAG TDL by means of a RR-GWS..... 76
- Figure 32: Characterization of a RD-GWS series as used in [Die15, Pie16]. Parameters are GWS sample number – duty cycle [%] – etching depth [nm] – grating sidewall angle [°]. .... 79
- Figure 33: Setup of the laser resonator as presented by [Die15, Pie16] for the intra-cavity generation of the second harmonic by a nonlinear conversion. The classical elements used to stabilize polarization and wavelength of the radiation in the resonator were replaced by a single RD-GWS which allowed obtaining a new record in output power and efficiency..... 80
- Figure 34: SEM image of the cleaved 5-30-10 GWS. SEM images were provided by AMO GmbH. .... 82
- Figure 35: Measured and simulated reflectivity of the RR-GWS 7-30-10. .... 83
- Figure 36: GWS#1, measured distribution of the DE for different total exposure times (10s, 30s, and 70s) to the wet-etching process as described in [Dan14, Dan18]. ..... 85
- Figure 37: GWS#2, measured distribution of the DE for different total exposure times (60s, 120s, and 180s) to the wet-etching process described in [Dan14, Dan18]. ..... 86